

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 June 2002 (27.06.2002)

PCT

(10) International Publication Number
WO 02/49892 A1

(51) International Patent Classification⁷:
F03G 1/02, 7/08, F16D 61/00, 63/00

B60T 1/10,

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(21) International Application Number: PCT/SE01/02808

(22) International Filing Date:
18 December 2001 (18.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0004716-7 20 December 2000 (20.12.2000) SE

(71) Applicant (*for all designated States except US*): HALDEX
BRAKE PRODUCTS AB [SE/SE]; Box 501, S-261 24
Landskrona (SE).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report


(72) Inventor; and

(75) Inventor/Applicant (*for US only*): SEVERINSSON,
Lars [SE/SE]; Nordanåvägen 27, S-310 21 Hishult (SE).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(74) Agent: STRÖM & GULLIKSSON IPC AB; Box 4188,
S-203 13 Malmö (SE).

(54) Title: A SPRING BRAKE ACTUATOR



(57) Abstract: A spring brake actuator is mounted with its shaft (11) connected to the rotational operative shaft of a service brake actuator. The spring brake actuator has a clock spring (14), which is mechanically charged at a rotation of the actuator shaft in a brake release direction. It also has an electric coil (15) for keeping when electrically energized - the clock spring in its charged condition. Further, it has means (12, 24, 18-22) for transferring the rotative energy of the clock spring to the actuator shaft in a brake applying direction, when the coil is energized, but allowing free rotation of the shaft in either direction, when the coil is energized.

WO 02/49892 A1